

Ura

ref. **UR104**

Pendant lamp
Lámpara colgante

28cm | 11in

Ø8cm | 3,2in

150cm | 59,1in



Ø50cm | 19,7in

Ura Collection



UR01



UR03



UR104



UR204



UR304



UR04-3

MATERIAL FINISHES MATERIALES Y ACABADOS

LAMPSHADE

TULIPA

Painted stainless steel
Acero inoxidable pintado

One colour to choose
Un color a elegir



*For orders of 5 or more units select any color NCS
*A partir de 5 unidades elegir color NCS

CANOPIE AND CABLE




FLORÓN Y CABLE

Steel gloss nickel-plated
Acero níquel-satinado



Black or transparent cable
Cable negro o transparente

LIGHT SOURCE FUENTE DE LUZ

230V - 50Hz

-  E27 - Max. 1x100 W
-  E27 LED - Max. 1x12 W
-  E27 ECO - Max. 1x77 W

120V - 60Hz

-  E26 Med. - Max. 1x100 W
-  E26 Med. - Max. 1x42 W

ENERGY EFFICIENCY EFICIENCIA ENERGÉTICA

from A+ to E
desde A+ a E

OTHER TECHNICAL DATA OTROS DATOS TÉCNICOS

PACKAGING

EMBALAJE

61x61x32cm | 24x24x12,6in
3,9kg | 8,6lb

ELECTRICAL FEATURES CARACTERÍSTICAS ELÉCTRICAS



CERTIFICATIONS CERTIFICACIONES



Ura

LED

ref. **UR104-LD**

LED / DIMMABLE

Pendant lamp

Lámpara colgante

Ø14,2cm | 5,6in

150cm | 59,1in

28cm | 11in



Ø50cm | 19,7in

Ura Collection



UR01



UR03



UR104



UR204



UR304



UR04-3

MATERIAL FINISHES MATERIALES Y ACABADOS

LAMPSHADE

TULIPA

Painted stainless steel
Acero inoxidable pintado

One colour to choose
Un color a elegir



*For orders of 5 or more units select any color NCS

*A partir de 5 unidades elegir color NCS

CANOPY AND CABLE

FLORÓN Y CABLE

Steel gloss nickel-plated
Acero níquel-satinado

Black or transparent cable
Cable negro o transparente

LIGHT SOURCE FUENTE DE LUZ

230V - 50Hz

⊕ 18,1W 3000K 1776lm built-in
upon request 2700K 1645lm

Dimming system: DALI / Switch DIM
upon request PHASE CUT

120V - 60Hz

⊕ 18,1W 3000K 1776lm built-in
upon request 2700K 1645lm

Dimming system: 0-10V

ENERGY EFFICIENCY EFICIENCIA ENERGÉTICA

from A++ to A
desde A++ a A

OTHER TECHNICAL DATA OTROS DATOS TÉCNICOS

PACKAGING

EMBALAJE

61x61x32cm | 24x24x12,6in
4,4kg | 9,7lb

ELECTRICAL FEATURES

CARACTERÍSTICAS ELÉCTRICAS



CERTIFICATIONS

CERTIFICACIONES

