


GATCPAC

Josep Torres Clavé, 1931 Floor Lamp





Indirect floodlight with an adjustable shade, expressing the usefulness of machines to human life. A worldly object made entirely of aluminium and giving off a taste of history.

GENERAL DESCRIPTION

Metal polished aluminium structure with adjustable lampshade. Electric cable length: 2m / 78.7"

LIGHT SOURCE

Recommended light sources (adjustable): LED bulb: 17W

Compact fluorescent: 20W Incandescent: Max. 150W

E27 - E26 (Max. hgt.: 160 mm/ 6.3")

Light source not included. Dimmer included. Lamp suitable only for indoor use. Compatible with bulbs of the Energy efficiency class (E.E.C): A++... E. Always use the light source recommended or equivalent.

Input voltage: 100, 120, 230 VAC (50Hz / 60 Hz) According to destination.



APROXIMATE WEIGHT (unpacked)

11,3 Kg / 24.9 lb

REGULATIONS

 ϵ

 $_{\text{C}} (U_{\text{L}})_{\text{US}}$

IP 20 Non class 2 Dry location only

UNE-EN 60598 UNE-EN 55015 UL-153

UNE-EN 60529

E-352592

MAINTENANCE

OTHERS

Clean with a smooth cloth. It is advised not to use any ammonia, solvent or abrasive products.

The lamp is delivered in different packages. The assembly instructions are delivered with the product.

MODEL

